

---

# **aiolambda**

***Release 0.2.7***

**Dec 22, 2018**



---

## Contents:

---

|          |                                   |           |
|----------|-----------------------------------|-----------|
| <b>1</b> | <b>Quickstart</b>                 | <b>1</b>  |
| 1.1      | Requirements: . . . . .           | 1         |
| 1.2      | Create <i>project</i> : . . . . . | 1         |
| 1.3      | API specs: . . . . .              | 1         |
| 1.4      | Code . . . . .                    | 2         |
| 1.5      | Useful commands: . . . . .        | 2         |
| <b>2</b> | <b>Template init</b>              | <b>3</b>  |
| <b>3</b> | <b>Template update</b>            | <b>5</b>  |
| <b>4</b> | <b>Database</b>                   | <b>7</b>  |
| <b>5</b> | <b>AMQP</b>                       | <b>9</b>  |
| <b>6</b> | <b>Roadmap</b>                    | <b>11</b> |
| <b>7</b> | <b>Aiolambda-cli</b>              | <b>13</b> |
| <b>8</b> | <b>Indices and tables</b>         | <b>15</b> |



### 1.1 Requirements:

- **docker**
- **python3**
- **pip3**
- **aiolambda-cli:** *pip install -U aiolambda*

### 1.2 Create *project*:

Use *aiolambda-cli* to initialize project dir:

```
$ aiolambda-cli init jwt
```

### 1.3 API specs:

Define microservice [OpenAPI specs](#), for example:

```
/auth/{user_id}:  
  get:  
    tags:  
      - auth  
    summary: Return JWT token  
    operationId: jwt.handlers.auth_handler  
    parameters:  
      - name: user_id  
        description: User unique identifier
```

(continues on next page)

(continued from previous page)

```
in: path
required: true
example: 12
schema:
  type: integer
responses:
  '200':
    description: JWT token
    content:
      'application/json':
        schema:
          type: string
```

## 1.4 Code

Define your custom handlers referenced in *openAPI specs*. For example, *auth\_handler*:

```
async def auth_handler(user_id: str) -> Response:
    return compose(
        generate_token,
        logger.debug,
        return_200)(user_id)
```

## 1.5 Useful commands:

- *make lint*
- *make run*
- *make test*

See example *jwt* [README.md](#):

## CHAPTER 2

---

Template init

---

TODO





## CHAPTER 3

---

Template update

---



## CHAPTER 4

---

### Database

---

TODO



## CHAPTER 5

---

AMQP

---

TODO



- **Add more examples:**
  - **crud\_users: postgres.** Postgres calls. \*Document project: [page:database:postgres]
  - **user\_settings: mq.** Send and subscribe AMQP messages. \*Document project: [page:amqp]
  - **jwt: ci integration.** Basic CI integration with travis. \*Document project: [page:ci:travisci]
  - **jwt: container integration.** Basic container integration. \*Document project: [page:containers:docker:]
  - **jwt: functional implementations.** Async compose, types: errors, **ROP** documentation. \*Document project: [page:functional]
- **Change command definitions:**
  - **inputs:** Command defined with env vars, not cli commands (only use cli commands for short commands [big execution number of times]).
  - **updates:** Makes with inline, replace based ansible filters. (same things: number\_of\_postgres versions, etc. . . with default values)
  - **.env:** Recomend .env for auto updates and load envvars in each directory (*projects*).
- **Contributions:**
  - **databases:**
    - \* redis. . .
    - \* mongo. . .
  - **containers:**
    - \* firecracker. . .
  - **code analysis:**
    - \* code climate
  - **automated api tests:**

- \* **dredd**
- aiolambda functional



## CHAPTER 7

---

### Aiolambda-cli

---

```
Usage:
  aiolambda-cli init [--db=<name>] [--mq] [--ci] <project-name>
  aiolambda-cli [-h]
Options:
  -h --help          Show this screen.
  --version          Show version.
  --db=<name>        Database to include: [postgresql].
  --mq              Include RabbitMQ/AMQP client library.
  --ci              Include Travis-CI configuration.
```



## CHAPTER 8

---

### Indices and tables

---

- `genindex`
- `search`